

Layers of innovation. One solution at a time.

Tapes, liquid adhesives, and conductive adhesives from 3M help address multiple design challenges across a range of smartphone design applications. Explore 3M bonding solutions and EMI management solutions for enclosures, displays, FPCs, camera lenses and more.

- **Cover glass bonding** requires both high adhesion and shock absorbing capabilities to help prevent accidental glass damage. Bonding solutions from 3M offer **secure bonding for edge-to-edge displays** with minimal bonding areas.
- **Back covers** are tasked with both showcasing crucial design elements and protecting internal components. We offer a range of **high-strength tapes** addressing different design obstacles – from impact, water, or chemical resistance to reworkability and curved surface designs.
- **Ultra-thin display panel bonding tapes** from 3M can help **navigate foldable and curved devices** and offer excellent levels of anti-lifting, oxidation resistance, conformability, and cleanliness.
- **FPC bonding tapes** from 3M hold firm while tackling a variety of different design challenges such as adhering to curved surfaces, hard-to-bond surfaces like polyimide and resisting heat where it is needed most.
- Tapes and liquid adhesives from 3M are ready to **help protect intricate camera components** from the effects of daily use such as drops and spills.
- Conductive adhesives from 3M deliver a broad spectrum of performance – from **EMI shielding in the bond line gap for faraday cage designs** and high frequency RF noise attenuation to providing low **contact resistance** and electrical **conductivity for grounding designs**. With a range of conductive tapes, work with 3M to help find an ideal solution to help reduce EMI when there is contact between commonly used metals such as stainless steel or aluminum.

Smartphone Applications

No.	Application Idea	No.	Application Idea	No.	Application Idea
1	Display shielding	8	Antenna Bonding	15	Camera bonding (lens)
2	Display EMI absorption	9	PCB shielding	16	Foam lamination (not shown)
3	Display module bonding	10	Camera shielding	17	Mesh bonding (not shown)
4	Cover display bonding	11	Back cover bonding	18	Silicone bonding (not shown)
5	Battery bonding	12	Component grounding	19	Packaging (not shown)
6	FPC bonding	13	Logo bonding		
7	FPC grounding	14	Camera bonding (deco)		



	Number	Application	Use ideas	Featured Product Number	Product Type	Color	Thickness (µm)	Features
Smartphone	1	Display shielding	Display FPC shielding	1050TC	Single Sided Copper Foil Tape	Copper	15/18/20/25	<ul style="list-style-type: none"> • XYZ-conductivity • Conformable, quick bonding • Copper foil backing
				1020BC	Single Sided Conductive Black Foil Tape	Black	10/20/25	<ul style="list-style-type: none"> • XYZ-conductivity • Conformable, quick bonding • Black copper foil backing
	2	Display EMI absorption	Display FPC/ back side EMI absorption	EM25TP	Absorber	Black	25/35/50/150/200/250	<ul style="list-style-type: none"> • Targeted permeability for < 5-10MHz FFDM performance • Excellent absorbing performance from 100MHz to 4 GHz • Black PET top film layer and PSA are optional
	3	Display module bonding	Glass fiber reinforced plastic to metal bonding	74xxxNH	Adhesive Transfer Tape	Clear	25/75/110/200	<ul style="list-style-type: none"> • Low modulus at RT & lower temperature • High temperature and humidity resistance • Good liner release properties for convertibility
				UCT-xx	Double Coated PET Tape	Clear	10/20/30/50	<ul style="list-style-type: none"> • Ultra clear • High initial adhesion • Produced in a clean room, easily converted
	4	Cover display bonding	Ink-coated glass to metal, glass fiber reinforced plastic to metal, metal to metal	VHB™ 5981	Acrylic Foam PET Tape	Black	200/250/300/350/400	<ul style="list-style-type: none"> • Good reworkability • Impact resistance and conformability • Easily converted"
				VHB™ 590x	Acrylic Foam Tape	Black	150/200/250/300/350	<ul style="list-style-type: none"> • High bonding strength and durability • Conformable • Seal against water ingress
				VHB™ 864xx*	Acrylic Foam Tape	Black	150/200/250/300	<ul style="list-style-type: none"> • High bonding strength • Impact resistance • Conformable
			Cpper film to PBT or anodized aluminum	94130HD*	PE Foam Tape	Black	300	<ul style="list-style-type: none"> • Good rework performance by heat • Impact resistance • High push out force and anti-lifting • Good compression and sealing

*Sample available globally, however sales is limited to Asia

Chart continued on next page

	Number	Application	Use ideas	Featured Product Number	Product Type	Color	Thickness (µm)	Features
Smartphone	5	Battery bonding	Plastic film to metal alloy	552xxP/BP	Double Coated PET Tape	Clear, Black	50/75/100/120	<ul style="list-style-type: none"> • High initial adhesion • Good shear holding power • Easily converted
				9628B, 9629B	Double Coated PET Tape	Black	50, 100	<ul style="list-style-type: none"> • Excellent adhesion to difficult to bond surfaces • Easily converted
				VHB™ 864xx*	Acrylic Foam Tape	Black	150/200/250/300	<ul style="list-style-type: none"> • High bonding strength • Impact resistance • Conformable
				950xx	Adhesive Transfer Tape	Black	50/100	<ul style="list-style-type: none"> • Impact resistance and damping • High bonding strength • Conformable, removable
	6	FPC bonding	FPC to plastic	9471LE, 9472LE	Adhesive Transfer Tape	Clear	58, 132	<ul style="list-style-type: none"> • Bonding to low surface energy substrates • Anti-lifting • Resistance to chemicals, moisture and humidity
				GTM7xxP/BP	Double Coated PET Tape	Clear, Black	50/80/100/150/200/250	<ul style="list-style-type: none"> • Bonding to low surface energy substrates • High peel strength • Anti-repulsion, easily converted
				9077	Double Coated Tissue Tape	Clear	50	<ul style="list-style-type: none"> • 260°C short-term heat resistance • Releasable after lead-free solder reflow • High adhesion and holding power
	7	FPC grounding	FPC to back cover/metal part grounding	9701	Double Sided Non-woven Conductive Tape	Grey	50/100	<ul style="list-style-type: none"> • XYZ-conductivity • Good electrical contact to small area • Nickel/copper-coated conductive non-woven fabric carrier
				9711S	Double Sided Conductive Fabric Tape	Grey	30/50/80/100/120/130/150/170/200/210/220/250/300	<ul style="list-style-type: none"> • XYZ-conductivity • Excellent conformability, quick bonding • Nickel/copper-coated conductive fabric and conductive PSA
	8	Antenna Bonding	Antenna FPC to metal	81504	Adhesive Transfer Tape	Clear	38	<ul style="list-style-type: none"> • Low and stable dielectric constant • High adhesion • High temperature and humidity resistant
				467MP, 468MP	Adhesive Transfer Tape	Clear	60, 130	<ul style="list-style-type: none"> • Up to 204°C short-term heat resistance • Solvent resistance • High shear strength
				9471LE, 9472LE	Adhesive Transfer Tape	Clear	58, 132	<ul style="list-style-type: none"> • Bonding to low surface energy substrates • Anti-lifting • Resistance to chemicals, moisture and humidity

*Sample available globally, however sales is limited to Asia

Chart continued on next page

	Number	Application	Use ideas	Featured Product Number	Product Type	Color	Thickness (µm)	Features
Smartphone	9	PCB shielding	Shielding can lid replacement	3304BC-S	Single Sided Conductive Black Foil Tape	Black	45	<ul style="list-style-type: none"> • XYZ-conductivity, conformable • Excellent EMI/ESD and electrical performance over time • Scratch resistant black copper foil carrier
	10	Camera shielding	Camera PCB/FPC shielding	1050TC	Single Sided Copper Foil Tape	Copper	15/18/20/25	<ul style="list-style-type: none"> • XYZ-conductivity • Conformable, quick bonding • Copper foil backing
				3304BC-S	Single Sided Conductive Black Foil Tape	Black	45	<ul style="list-style-type: none"> • XYZ-conductivity, conformable • Excellent EMI/ESD and electrical performance over time • Scratch resistant black copper foil carrier"
	11	Back cover bonding	Ink-coated glass to metal or glass fiber reinforced plastic to metal	VHB™ 590x	Acrylic Foam Tape	Black	150/200/250/300/350	<ul style="list-style-type: none"> • High bonding strength and durability • Conformable • Seal against water ingress
				5126*	PE Foam Tape	Black	250/300/350	<ul style="list-style-type: none"> • Waterproofing • Anti-lifting • High push out force and impact resistance
				VHB™ 864xx*	Acrylic Foam Tape	Black	150/200/250/300	<ul style="list-style-type: none"> • High bonding strength • Impact resistance • Conformable
	12	Component grounding	Component grounding to metal frame	9711S	Double Sided Conductive Fabric Tape	Grey	30/50/80/100/120/130/170/200/210/220/250/300	<ul style="list-style-type: none"> • XYZ-conductivity • Excellent conformability, quick bonding • Nickel/copper-coated conductive fabric and conductive PSA
	13	Logo bonding	Ink-coated metal to metal	961xxCR	Adhesive Transfer Tape	Clear	25/50	<ul style="list-style-type: none"> • Chemical resistance • Produced in a clean room
				VHB™ 590x	Acrylic Foam Tape	Black	150/200/250/300/350	<ul style="list-style-type: none"> • High bonding strength and durability • Conformable • Seal against water ingress
	14	Camera bonding (decoration)	Ink-coated plastic (or glass) to plastic (or metal) bracket bonding	950xx	Adhesive Transfer Tape	Black	50/100	<ul style="list-style-type: none"> • Impact resistance and damping • High bonding strength • Conformable, removable
				9471LE, 9472LE	Adhesive Transfer Tape	Clear	58, 132	<ul style="list-style-type: none"> • Bonding to low surface energy substrates • Anti-lifting • Resistance to chemicals, moisture and humidity
				467MP, 468MP	Adhesive Transfer Tape	Clear	60, 130	<ul style="list-style-type: none"> • Up to 204°C short-term heat resistance • Solvent resistance • High shear strength

*Sample available globally, however sales is limited to Asia

Chart continued on next page

	Number	Application	Use ideas	Featured Product Number	Product Type	Color	Thickness (µm)	Features
Smartphone	15	Camera bonding (lens)	Ink-coated glass to metal bracket bonding	VHB™ 4914	Acrylic Foam Tape	White	150/200/250	<ul style="list-style-type: none"> Waterproofing High bonding strength and long-term durability
			Ink-coated glass to plastic	950xx	Adhesive Transfer Tape	Black	50/100	<ul style="list-style-type: none"> Impact resistance and damping High bonding strength Conformable, removable
				VHB™ 5980*	Acrylic Foam Tape	Black	150/200/250/300	<ul style="list-style-type: none"> Drop shock and impact resistance Conformable Seal against water and moisture
	16	Foam lamination	PE foam (or PET film) to plastic	552xxP/BP	Double Coated PET Tape	Clear, Black	50/75/100/120	<ul style="list-style-type: none"> High initial adhesion Good shear holding power Easily converted
				GTM7xxP/BP	Double Coated PET Tape	Clear, Black	50/80/100/150/200/250	<ul style="list-style-type: none"> Bonding to low surface energy substrates High peel strength Anti-repulsion, easily converted
				UCT-xx	Double Coated PET Tape	Clear	10/20/30/50	<ul style="list-style-type: none"> Ultra clear High initial adhesion Produced in a clean room, easily converted
				9471LE, 9472LE	Adhesive Transfer Tape	Clear	58, 132	<ul style="list-style-type: none"> Bonding to low surface energy substrates Anti-lifting Resistance to chemicals, moisture and humidity
	17	Mesh bonding	Mesh to plastic or PU foam	9628B, 9629B	Double Coated PET Tape	Black	50, 100	<ul style="list-style-type: none"> Excellent adhesion to difficult to bond surfaces Easily converted
	18	Silicone bonding	Silicone part to plastic	9119	Double Coated PET Tape	Clear	50/100/140	<ul style="list-style-type: none"> Bonding to silicone substrates Good shear holding power Easily converted
				9731	Double Coated PET Tape	Clear	50/100/140	<ul style="list-style-type: none"> Bonding to silicone substrates High temperature and chemical resistance
	19	Packaging	Paper bonding	9448A, 9080A	Double Coated Tissue Tape	White, Clear	150	<ul style="list-style-type: none"> High initial adhesion Up to 150°C short-term heat resistance Easily converted
				SP7202	1K Screen Printable Adhesive	Clear	-	<ul style="list-style-type: none"> Screen printable, high shear strength UV curable in seconds Solvent free (100% solids)

*Sample available globally, however sales is limited to Asia

Safety Data Sheet: Consult Safety Data Sheet before use.

Regulatory: For regulatory information about this product, contact your 3M representative.

Technical Information: The technical information, recommendations and other statements contained in this document are based upon tests or experience that 3M believes are reliable, but the accuracy or completeness of such information is not guaranteed.

Product Use: Many factors beyond 3M's control and uniquely within user's knowledge and control can affect the use and performance of a 3M product in a particular application. Given the variety of factors that can affect the use and performance of a 3M product, user is solely responsible for evaluating the 3M product and determining whether it is fit for a particular purpose and suitable for user's method of application.

Warranty, Limited Remedy, and Disclaimer: Unless a different warranty is specifically stated on the applicable 3M product packaging or product literature, 3M warrants that each 3M product meets the applicable 3M product specification at the time 3M ships the product. **3M MAKES NO OTHER WARRANTIES OR CONDITIONS, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY OR CONDITION ARISING OUT OF A COURSE OF DEALING, CUSTOM, OR USAGE OF TRADE.** If a 3M product does not conform to this warranty, then the sole and exclusive remedy is, at 3M's option, replacement or repair of the 3M product or refund of the purchase price.

Limitation of Liability: Except where prohibited by law, 3M will not be liable for any loss or damage arising from the 3M product, whether direct, indirect, special, incidental, or consequential, regardless of the legal or equitable theory asserted, including, but not limited to, warranty, contract, negligence, or strict liability.

Disclaimer: For industrial use only. Not intended, labeled or packaged for consumer sale or use.



Electronics Device Bonding
3M Center, Building 225-3S-06
St. Paul, MN 55144-1000

Phone 1-800-362-3550
Web www.3M.com/electronicbonding

3M and VHB are trademarks of 3M Company.
Please recycle. © 3M 2022. All rights reserved.
60-5005-0393-7



SNT International Pvt. Ltd.

SNT International Private Limited.
94, Toycity Ecotech—III, Greater
Noida , (U.P.) INDIA
Phone— 9810139406